



Hydraulics

Machinery

Retail

Tractor

Transmission

partrite

PRODUCT NEWS

www.partrite.co.za

No. 20 / 2009

SPRAYER UNITS

TR2-720R

Technical specifications:

- Sprayer unit in Galvanised steel plate with Ø 720 mm internal
- Comer gearbox model D-27A (ratio 1:3,5 – 1:5,25)
- Staunch closed aluminium fan with special plastic blades (9 blades)
- With centrifugal clutch
- Stainless steel manifolds with clamps
- Braglia® M92 spray nozzles (12 nozzles)
- Twin Air Port System
- From 23.000 to 30.000 m³/h and from 16 to 27 hp (25° to 45°)



TR2D-820R

Technical specifications:

- Sprayer unit in Galvanised steel plate with Ø 820 mm internal
- Priority steel deflector
- Comer gearbox model D-21A (ratio 1:3,6 – 1:4,5)
- Staunch closed aluminium fan with special plastic blades (8 blades)
- With centrifugal clutch
- Stainless steel manifolds with clamps
- Braglia® M92 spray nozzles (14 nozzles)
- Twin Air Port System
- From 35.000 to 45.000 m³/h and from 22 to 36 hp (25° to 45°)



TR2D-920R

Technical specifications:

- Sprayer unit in Galvanised steel plate with Ø 920 mm internal
- Priority steel deflector
- Comer gearbox model D-21A (ratio 1:3,6 – 1:4,5)
- Staunch closed aluminium fan with special plastic blades (10 blades)
- With centrifugal clutch
- Stainless steel manifolds with clamps
- Braglia® M92 spray nozzles (16 nozzles)
- Twin Air Port System
- From 40.000 to 54.000 m³/h and from 29 to 52 hp (25° to 45°)

